



Equideck Grids

Specification Sheet

We are proud to offer 100% recycled, UK manufactured, eco-friendly ground reinforcement grids to provide an excellent, easy to use, but professional remedy for stability and achieve S.U.D.S compliant surfaces.

Our high-quality, sustainable grids offer stability for a variety of uses including driveways, parking areas, grassland, building bases and more for domestic and commercial purposes.



PRODUCT INFORMATION

Material	100% recycled, black, non toxic, UV stable PP/PE blend
Dimensions	500mm x 500mm x 40mm
Rib Wall Thickness	3.5mm
Weight/m2	4kg
No Grids/m2	4
Filling	Gravel, Stone, Grass, Grass Seed, Soil, 3mm-30mm
Temperature Stability	-50°C to 90°C
Fitting	4 integrated V force push fit locking connections per side
Environmental	Complies with S.U.D.S & Flood & Water Management Act 2010
Country of Manufacture	UK
Shipping Details	260 grids / 65 sqm per pallet 500 tonnes load capacity
Vehicle Testing	Tested to withstand vehicles up to 30 tonnes
Compression Test	500 tonne
Axle Load	30 tonnes
Extra	Built in anti-migration cell bottom lattice and anti-gravel movement ribs, cell-wall topped anti-slip nodules. Used on slop inclines of in excess of 1 in 4.