



Shed & Building Bases

Specification Sheet

We are proud to offer 100% recycled, UK manufactured, eco-friendly ground reinforcement grids to provide an excellent, easy to use, but professional remedy for stability and achieve S.U.D.S compliant surfaces.

Our high-quality, sustainable grids offer stability for a variety of uses including driveways, parking areas, grassland, building bases and more for domestic and commercial purposes.

If you have purchased membrane please look at the geotextiles spec sheet.



PRODUCT INFORMATION

Material	100% recycled, black, non toxic, UV stable PP/PE blend
Dimensions	500mm x 500mm x 40mm
Rib Wall Thickness	3.5mm
Weight/m2	4kg
No Grids/m2	4
Filling	Gravel, Stone, Grass, Grass Seed, Soil, 3mm-30mm
Temperature Stability	-50°C to 90°C
Fitting	4 integrated V force push fit locking connections per side
Environmental	Complies with S.U.D.S & Flood & Water Management Act 2010
Country of Manufacture	UK
Shipping Details	260 grids / 65 sqm per pallet 500 tonnes load capacity
Vehicle Testing	Tested to withstand vehicles up to 30 tonnes
Compression Test	500 tonne
Axle Load	30 tonnes
Extra	Built in anti-migration cell bottom lattice and anti-gravel movement ribs, cell-wall topped anti-slip nodules. Used on slop inclines of in excess of 1 in 4.

